



## hdmi connection cable

### Product introduction

The DKT CC-HDMI-x series of HDMI 1.4b Category 2 connection cables has been developed to minimize the need for separate Ethernet and audio cables. It copes well with the increasing number of interference sources in subscriber home installations. The DKT series of HDMI cables allows distribution of Ethernet to peripheral devices through the HDMI cable through HDMI Ethernet Channel. Cable designs are tested in accordance with the HDMI Compliance Test Specification, (category 2 High Speed HDMI®/™ Cable) at an HDMI authorized test center.



Type no.	Item no.	Length
CC-HDMI-1,5	20186	1,5m
CC-HDMI-2	20187	2m
CC-HDMI-3	20188	3m
CC-HDMI-5	20189	5m

### Technical specifications

Electrical characteristics		CC-HDMI-1,5	CC-HDMI-2	CC-HDMI-3	CC-HDMI-5
HDMI version		1.4b category 2 (high speed)			
HDMI Ethernet Channel support		Yes			
Audio Return Channel support		Yes			
Video performance		1080p, 3D, 4K, deep color			
Physical characteristics					
Inner conductor	Ø mm	CU 0.203	CU 0.203	CU 0.254	CU 0.32
Insulation	Ø mm	FM PE 0.53/1P		FM PE 0.65/1P	FM PE 0.85/ 0.87/1P
		HDPE 0.50/4C		HDPE 0.55/4C	HDPE 0.75/4C
Drain wire	Ø mm	CU 0.203	CU 0.203	CU 0.254	CU 0.32
AL/MY		AL/MY+MYLAR*4+1C			
S.FOIL		S.FOIL			
Braid shield	Ø mm	AL-MG 0.12*3/16			
Black Outer Jacket	Ø mm	5	5	6	7.3
Jacket material		Black PVC			
Outer sheath	Ø mm	5	5	6	7.3