

Description

Halogen free, low smoke emission coaxial cable - 75 Ohm

Outdoor installation cable (Screening Class A+)

Coaxial Cables

CAVEL

since 1968

Data Sheet**DG113ZHB**

Ø	1,13	4,80	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet/Al)	(CuSn)	(LSZH)

Standards

EN 50117-2-5

Construction data

Inner conductor of plain copper	(Cu)	1,13 ± 0,02 mm
Dielectric of physical foam polyethylene	(PEG)	4,80 ± 0,10 mm
Water repellent sealing (dielectric)	(Jelly1)	
Aluminium/Polyester/Aluminium tape longitudinally overlapped	(Al/Pet/Al)	
Braid of tinned copper wires	(CuSn)	
Braid optical coverage (IEC 96-1)		72 %
Diameter under Sheath		5,30 mm
Outer sheath of Thermoplastic material - white - halogen-free, low smoke, flame retardant and UV-resistant	(LSZH)	6,60 ± 0,10 mm

Printed each meter by blue ink-jet :

**CAVEL DG 113 ZHB MADE IN ITALY 75 Ohm EN50117-2-5 CEI-UNEL 36762 C-4 (U0 =400V) * LTE
PROTECTION * ss/aa m**

(ss=week, aa=year) (m=meter marking)

Physical data

Weight of copper conductors	19,20	kg/km
Total weight of cable	43,38	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	150	N

ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date**16/05/2011****Responsible****Alberto Scardovi**

Description

Halogen free, low smoke emission coaxial cable - 75 Ohm

Outdoor installation cable (Screening Class A+)

**Data Sheet****DG113ZHB****Electrical data**

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		13,90	Ohm/km
Loop resistance		31,90	Ohm/km
Insulation voltage of the sheath (spark test)		3	kV
Maximum current (Ieff)		8	A

Structural return loss (SRL)

5 - 470 MHz	>30 dB
470 - 1000 MHz	>28 dB
1000 - 2000 MHz	>26 dB
2000 - 3000 MHz	>22 dB

Screening Attenuation (SA)

30 - 1000 MHz	>95 dB
1000 - 2000 MHz	>90 dB
2000 - 3000 MHz	>80 dB

Transfer impedance

5 - 30 MHz < 2,5 mΩ/m

Attenuation (at 20°C)

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,60	862	17,10
10	2,10	1000	18,50
30	3,20	1750	24,90
50	4,10	2150	27,90
200	7,90	2400	29,60
300	9,80	3000	33,40
470	12,40		

ITALIANA CONDUTTORI s.r.l.Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

16/05/2011

Responsible

Alberto Scardovi

Description

Halogen free, low smoke emission coaxial cable - 75 Ohm

Outdoor installation cable (Screening Class A+)




Data Sheet

DG113ZHB

Attenuazione di schermatura / Screening Attenuation

Cavo classe A+ / A+ Class Cable

Cavo tipo / Cable type : **DG 113 ZH**



ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli
Tel +39-382.815150 Fax +39-0382.814212

Date

16/05/2011

Responsible

Alberto Scardovi