

## outdoor and indoor cables

DKT provides an extensive range of coaxial cables for indoor and outdoor installation, most of these being manufactured by Cavel. Cavel has produced cables since 1968, and offers a 15 year warranty on its Cavel branded cables. All cables have 75 Ohm impedance, which is suitable for CATV networks.



### Outdoor cables

Cable	Item no	Package	Dimensions (mm)	Attenuation (dB/100m)	Screening Attenuation
DKT SAT 1S	00100	250m	1.63 / 7.2 / 10.1	13.0	Class A
DKT SAT 1S	00106	500m	1.63 / 7.2 / 10.1	13.0	Class A
DG163ZH	00130	500m	1.63 / 7.2 / 10.1	13.0	Class A+
DKT 22/99 FC	00614	250m	2.20 / 9.9 / 12.7	9.8	Class A
DKT 22/99 FC	00615	500m	2.20 / 9.9 / 12.7	9.8	Class A
DKT 22/99 ZH	00631	250m	2.20 / 9.9 / 12.7	9.8	Class A
DKT 17/73 FC	00616	250m	1.63 / 7.2 / 10.1	12.8	Class A
DKT 11/48L-Light	00618	500m	1.13 / 4.8 / 7.6	18.5	Class A
DKT 11/48	00619	500m	1.13 / 4.8 / 7.6	18.5	Class A
DKT 11/48	00633	250m	1.13 / 4.8 / 7.6	18.5	Class A
DKT 11/48	00622	100m	1.13 / 4.8 / 7.6	18.5	Class A
DKT 11/48+Pipe	00635	400m	1.13 / 4.8 / 7.6	18.5	Class A
DKT 34/145 FC	00621	700m	3.40 / 14.5 / 19.8	6.9	Class A
Coax4 CT22 S	00823	1000m	2.20 / 8.8 / 12.3	9.8	Class A++
Coax3 CT33 S	00833	500m	3.30 / 13.3 / 17.1	6.5	Class A++
Coax2 CT48 S	00848	500m	4.75 / 19.4 / 24.9	4.8	Class A++

### Indoor cables

Cable	Item no	Package	Dimensions (mm)	Attenuation (dB/100m)	Screening Attenuation
DKT SAT 1H	00105	250m	1.63 / 7.2 / 10.1	13.0	Class A
DG113ZHW-S100	00236	100m	1.13 / 4.8 / 6.6	18.5	Class A+
DG113ZHW-S250	00238	250m	1.13 / 4.8 / 6.6	18.5	Class A+
DG113ZH G	00753	100m	1.13 / 4.8 / 6.6	18.5	Class A+
DG135OHW-S100	00380	100m	1.13 / 4.8 / 6.7	18.9	Class A
DG135OHW-R100	00381	100m	1.13 / 4.8 / 6.7	18.9	Class A
DG135OHW-R25	00384	25m	1.13 / 4.8 / 6.7	18.9	Class A
DG135SOHW-100-BF	00390	100m	1.13 / 4.8 / 6.7	18.9	Class A
DG135SOHW-250-BF	00392	250m	1.13 / 4.8 / 6.7	18.9	Class A
Cavel CW41 S OHW	00720	100m	0.41 / 1.9 / 4.3	48.7	Class A
Cavel CW41 S OHW	00725	250m	0.41 / 1.9 / 4.3	48.7	Class A
DG800HW	00731	100m	0.80 / 3.5 / 5.0	25.5	Class A
DG800HW	00732	250m	0.80 / 3.5 / 5.0	25.5	Class A
DG123OHW	00752	100m	1.13 / 4.8 / 6.6	18.6	Class A
DG123OHW	00756	250m	1.13 / 4.8 / 6.6	18.6	Class A
DG123OHW	00759	500m	1.13 / 4.8 / 6.6	18.6	Class A