

INCREASE LIFETIME AND SERVICE ACTIVATION.

797XX SERIES | 10 Gbps Active Ethernet | XGSPON



FTTH NETWORKS

Further information on DKTCOMEGA.com

Sign up for our email newsletter and always be informed first!

SIGN UP

Version 1.2.0

DATASHEET

797XX SERIES | 10 Gbps Active Ethernet | XGSPON

INTRODUCTION

The DKT 797xx series is built to fit the well proven DKT FTU. The newly developed active part is based upon a sophisticated wirespeed Layer 2 switching-based “System-on-Chip” (SoC) solution. This solution implies that fiber termination and service activation occur as part of the operator’s “demarcation point” at the end customer in a FTTH 10 Gbps environment.

PRODUCT OVERVIEW

“797xx series”

Parameter			XGSPON		XGSPON with CATV		10G Epon with DPoE	
	FTTH-10G-1F-3P	FTTH-10G-2F-3P-CATV	FTTH-XGS-1F-3P	FTTH-XGS-1F-2P	FTTH-XGS-1F-3P-CATV	FTTH-XGS-1F-2P-CATV	FTTH-10G EPON-1F-3P	FTTH-10G EPON-1F-2P
10Gbps EPON WAN	-	-	-	-	-	-	✓	✓
10 Gbps WAN	✓	✓	-	-	-	-	-	-
XGSPON WAN	-	-	✓	✓	✓	✓	-	-
1 Gbps LAN	2	2	2	1	2	1	2	1
10 Gbps LAN	1	1	1	1	1	1	1	1
CATV	-	✓	-	-	✓	✓	✓	✓
Switch engine ²⁾	✓	✓	✓	✓	✓	✓	✓	✓
WDM filter	-	¹⁾	-	-	✓	✓	-	-
Fiber Connector	SC/UPC	SC/UPC + SC/APC	SC/APC	SC/APC	SC/APC	SC/APC	SC/APC (SC/UPC on request)	SC/APC (SC/UPC on request)
SFP WAN	✓	✓	✓	-	✓	-	✓	-
BOSA WAN	-	-	-	✓	-	✓	-	✓
Compatible with DKT clickable FTUs ³⁾	✓	✓	✓	✓	✓	✓	✓	✓
TR-069	✓	✓	-	-	-	-	-	-
Item No.	79751	79752	79757	79857	79759	79859	79761	79861

¹⁾ Option

²⁾ Support for VLANs, Q-in-Q, QoS, IGMP, Jumbo Frames and traffic shaping and manipulation

³⁾ All passive FTUs has to be ordered separately.

HIGH LEVEL SPECIFICATION

797XX SERIES | 10 Gbps Active Ethernet | XGSPON

PRODUCT RATIONALE

The industry terms this a “2 box solution”, where there is clear differentiation between FTU/CPE and the router/home gateway. This solution optimizes sourcing/logistics as well as support and technical upgrade which remains flexible and smooth, and allow operators to offer an FTTH infrastructure suitable for both a retail and wholesale business model.

The FTU layout is based on a standard euro outlet form factor, customer perceives this unit as an outlet, not “yet another appliance in my house”, and the active part can be clicked directly on top of the FTU.

The active unit comes with 1 x SC/ UPC + 1 x SC/APC (CATV option) for 10 Gbps Active Ethernet, and 1 x SC /APC for XGSPON (WDM built- in), based on a “none proprietary” solution, it can be adopted in environments with 3rd party equipment. It has low power dissipation, supporting the recommendation of “Code of Conduct on Energy Consumption of Broadband Equipment”.



Easy click-on
“2 box solution” with DKT FTUs



Interoperable
with third-party OLTs



HIGH LEVEL SPECIFICATION

797XX SERIES | 10 Gbps Active Ethernet | XGSPON

<p>System</p> <p>Cortina CA8271 Multi-protocol, 10 G SoC (System-on-Chip)</p> <p>128 MB NAND FLASH</p> <p>256 MB RAM</p>	<p>Layer 2 Ethernet</p> <p>Layer 2 wire speed</p> <p>IEEE 802.1 Q VLANs incl Q-in-Q</p> <p>IEEE 802.1 Q tag insertion and stripping</p> <p>DHCP relay/option 82</p> <p>IGMP v2/3 snooping</p> <p>Flow packet policing</p> <p>Traffic shaping</p> <p>Support for Jumbo Frames, 2k frames</p>	<p>Management</p> <p>DKT OS based on Linux, provisioning via DHCP/TFTP</p> <p>TR-069, incl. TR-181</p> <p>SNMP /2/3</p> <p>SSH</p> <p>HTTP(S) WEB</p>
<p>10Gbps WAN</p> <p>1x WAN SMF, IEEE 802.3ae</p> <p>10 GBASE-LR TX: 1270 nm; RX: 1330 nm;</p> <p>Range: 20 km</p> <p>Laser Class 1</p> <p>Optical Connector: SC/APC</p>	<p>CATV</p> <p>85 dBuV@-5 dBm, input</p> <p>Optical wavelength: 1310 ... 1550 nm</p> <p>Max optical input level: +3 dBm</p> <p>Typ operational optical input level: -10 ... -3 dBm</p> <p>Optical Connector: SC/APC</p> <p>RF flatness: <+/- 1 dB</p> <p>CNR: Typ. 49 dB</p> <p>CTB: > 60 dB</p> <p>CSO: > 60 dB</p> <p>F-connector, 75 Ohm</p>	<p>Physical Characteristics</p> <p>Operating temperatur: 0 °C ... 40 °C</p> <p>151 x 40 x 88 mm (HxDxW)</p> <p>Weight: < 0.5 kg</p> <p>Power</p> <p>USB-C adapter</p> <p>Europlug, white color (UK/US available upon request)</p> <p>Power dissipation: < 10 W</p> <p>LED: GREEN: Power on</p>
<p>XGSPON WAN</p> <p>1x WAN SFP+, ITU T G.9807.1</p> <p>X GSPON, Tx: 1270 nm, Rx: 1577 nm</p> <p>Range: 20 km</p> <p>Laser Class 1</p> <p>Optical Connector: SC/UPC</p> <p>1x WAN SFP+ applicable for 797xx series, 1x WAN BOSA applicable for 798xx series.</p>	<p>Monitoring</p> <p>Digital Optical Monitoring, SFF-8472</p> <p>OAM as option supporting IEEE 802.3 ah, Dying Gasp, Discovery and Loop-back</p>	<p>Approvals and Certifications</p> <p>CE marking, RoHS, WEEE</p> <p>Safety EN 60950</p> <p>Emission: EN55022:2010 Class B; EN 55032:2015</p>
<p>10 Gbps LAN</p> <p>1x RJ-45, support for 10 G BASE-T</p> <p>2 LEDs: - YELLOW: SPEED (10 Gbps); - GREEN: LINK/ACTIVITY</p>	<p>CATV signal level, higher/lower than -10 dBm</p>	<p>Immunity: EN 55024: 2010 + A1: 2015; EN 55035: 2017; EN 60728-2</p>
<p>1 Gbps LAN</p> <p>2x RJ-45, support for 10/10/1000 BASE-TX</p> <p>Auto-negotiating HD/FD</p> <p>Auto-MDI/MDIX</p> <p>2 LEDs: - YELLOW: SPEED (1 Gbps); - GREEN: LINK/ACTIVITY</p> <p>2x RJ-45 applicable for 797xx serie, 1x RJ-45 applicable for 798xx series.</p>		

FTTH-BATTERY-STD

PRODUCT OVERVIEW

“FTTH-Battery-STD”

Electrical parameter

Input	12 V; 3.3 A
Combined Output Power [W]	< 30
Output	12 ± 5 %V DC; < 2.5 A
USB	5 ± 5 %V DC; < 2 A
Transfer time	< 1 mS
3 cell Battery type	2600 mAH Lithium
Typical charge duration [h]	3 - 4

Mechanical parameters

Outer dimensions [mm]	130 x 67.3 x 27
Weight [g]	~400
Wall hang screw [mm]	Recommended (Not included): Flat head countersunk Pozi drive 3.5 x 25
Wall hang Screwhead Ø [mm]	5.5 - 6.5

In-Box accessories

150 cm USB A to DC Ø 5.5 mm/1.45 mm cable
150 cm DC to DC Ø 5.5 mm Cable

Environment

Operational temperature range [°C]	0 - 40
Humidity [%]	20 - 90
Recommended battery replacement cycle	1.5 - 2 years or 300 full charge/discharge cycles

Item No.

79731

ADDITIONAL INFORMATION

- Fast and easy battery installation
- Long lasting capacity
- Support for both 5 V/12 V, capable of sourcing both ONT and router
- compact form factor, discrete design
- Suitable for wall mount or desktop placement
- Exchangeable battery pack

