



Multimedia outlet



Type	MM4-85DX-F	MM4-85X-F
Item no.	52682	52683
Description	TV & Data Duplex Terminated	TV & Data Terminated
DATA		
Frequency Range Forward	118-1300 MHz	5-1300 MHz
Frequency Range Reverse	5-85 MHz	5-1300 MHz
Insertion loss, Forward	<5.5 dB	4.5 dB ± 1 dB
Insertion loss, Reverse	<1.4 dB	4.5 dB ± 1 dB
Isolation, Data-TV (5-87 MHz)	>45 dB	>45 dB
Isolation, DATA-TV	118-862 MHz: >21 dB	118-1300 MHz: >21 dB
TV		
Frequency Range (MHz)	118-1300 MHz	118-1300 MHz
Insertion loss	<5.5 dB	4.5 dB ± 1dB
General		
Connector	F-female	F-female
Return loss ¹ EN60728-4, IN, DATA, TV	Grade 2	Grade 2
Screening effectiveness ² EN50083-2	Class A	Class A
Dimension (H x W x D mm)	82 x 82 x 38	

According to CENELEC:

¹ Return loss Grade 2:

5-47 MHz ≥ 18 dB
47-1300 MHz min. 18 dB ÷ 1.5/oct.

² Screening effectiveness Class A:

5-300 MHz ≥ 85 dB
300-470 MHz ≥ 80 dB
470-950 MHz ≥ 75 dB
950-1300 MHz ≥ 55 dB



March 1st 2016

DKTCOMEGA

DKTCOMEGA
Fanoevj 6
DK-4060 Kirke Saaby

Tel +45 4646 2626
Fax +45 4646 2625
E-mail dkt@dktcomega.com
Web www.dktcomega.com