

Coax2 CT 48 S (4.75/19.4) IAD* LWT

CATV Trunk Cable



Application

CATV cables are used in trunk lines of CATV and broadband networks between headend and subscriber termination point. They are suitable for direct buried and duct laying. Coax LWT types are Longitudinal Water Tight.

Standards

EN 50117-2-3,
further EN 50083-2/A1, EN 50117-1
EN50289-4-2 method B

Flame resistance

IEC 60332-1 (not for cables with PE sheath)

Construction

Inner conductor	bare copper wire, diameter 4.75 mm
Insulation	IAD* gas injected foam PE, diameter 19.4 mm
Outer conductor	welded copper tube, diameter 20.0 mm
Sheath	PE, LWT (Longitudinal Water Tight), diameter 24.9 mm black
Printing	DRAKA - COAX2 CT 48 S LWT + meter marking + batch number

Mechanical properties

Minimum bending radius	without load	250 mm
	with load	500 mm
Temperature range	during operation	- 40° C to + 70° C
	during storage	- 40° C to + 70° C
	during installation	- 5° C to + 60° C
Tensile force		180 N
Longitudinal water tightness	according to EN 50289-4-2 method B	3m sample, water height 1m, 24h

Coax2 CT 48 S (4.75/19.4) IAD* LWT

Electrical properties

at 20°C

DC resistance	Inner conductor	1.0 Ω/km
	Outer conductor	0.95 Ω/km
Mutual capacitance		50 pF/m
Characteristic impedance		75 Ω ± 2 Ω
Velocity ratio		88 %
Screening attenuation	30 MHz – 1000 MHz	> 120 dB Screening Class A++
Transfer impedance	5 MHz – 30 MHz	< 0.9 mΩ/m Screening Class A++
Electrical strength	Dielectric	2.5 kV _{DC} 1 min
	Sheath	5 kV _{DC} 1 min

Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB) acc. to EN 50117-2-3	
Frequency (MHz)		Frequency (MHz)	
	nominal		nominal
5	0.28	5 – 30	≥ 30
10	0.39	30 – 470	≥ 30
30	0.68	470 - 1000	≥ 26
65	1.03		
80	1.14		
120	1.42		
200	1.85		
300	2.31		
400	2.71		
447	2.86		
450	2.87		
610	3.39		
700	3.65		
800	3.93		
862	4.10		

Technical data

Product code	Cable type	Weight kg/km	Standard delivery length m	Drum size		Copper content	Tensile force N	Storage
				Flange	Overall width			
	Coax2 CT 48 S LWT	560	500	1400	735	372	180	outside

[PRODUCT CODE TABLE]

Coax2 CT 48 S (4.75/19.4) IAD* LWT

© PRYSMIAN GROUP 2010, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.